Available online <u>www.jocpr.com</u>

Journal of Chemical and Pharmaceutical Research, 2014, 6(4):705-714



Research Article

ISSN: 0975-7384 CODEN(USA): JCPRC5

Synthesis and characterization of aliphatic-aromatic polyesters using interfacial polycondensation technique

Sangita G. Sanadhya*, S. L. Oswal[#] and Ketan C. Parmar*

*Sir P. T. Sarvajanik College of Science, Surat, Veer Narmad South Gujarat University, Gujarat, India # Department of Chemistry, Veer Narmad South Gujarat University, Gujarat, India

ABSTRACT

Thirteen linear aliphatic-aromatic polyesters were synthesized by interfacial polycondensation of various diacid chlorides such as adipoyl chloride (ADCL) and sebacoyl chloride (SECL) with various diols such as bisphenol-A (BPA), resorcinol (RES), 1,5-dihydroxy naphthalene(15DHN), 4,4'-bis(hydroxyl)benzilidine aniline (BHBA), 4,4'-bis(hydroxybenzilidine) benzidine(BHBB), 4,4'-bis (hydroxybenzilidine) -p- phenylene diamine (BHBP), 4,4'-bishydroxy biphenyl thioether (BHBPT) using chloroform-water interphase system, alkali as an acid acceptor and citramide as phase transfer catalyst at ambient temperature. The resulting polyesters were characterized by solubility test, elemental analysis, intrinsic viscosity measurements, FT-IR, and ¹H-NMR spectral analysis, and thermogravimetric analysis.

INTRODUCTION

Polyesters are important class of high performance and engineering polymers, which find use in a number of diverse applications [1-3]. Polyester is a strong fiber and consequently can withstand strong and repetitive movements. Its hydrophobic property makes it ideal for garments and jackets that are to be used in wet or damp environments. Coating the fabric with a water-resistant finish intensifies this effect. Since polyester can be moulded into almost any shape, certain insulating properties can be built in to the fiber. Polyester is used both as staple fiber as well as continuous filament yarns. Polyester staples are commonly used with cotton, wool, and rayon to get blended yarns. Polyester also has industrial uses as well, such as carpet, filters, synthetic artery replacements, ropes, and films. Further, they are also used as film forming, coating, adhesive and reinforced materials.

Different kinds of polyesters have been synthesized over the past decades from various types of diacid chlorides and diols. Thermally stable polyesters derived from isophthalic and terephthalic acids with bisphenol-A have been commercialized [4]. A polymeric resin was synthesized by the polycondesation technique of 4-hydroxybenzophenone and melamine with formaldehyde in the presence of 2M HCl as a catalys[5]. However, polyesters are generally difficult to process because of their limited solubility in organic solvents and their high melting temperature or high glass-transition temperature by virtue of their rigid structures. Chemically oxidation copolymerization of aniline and o-chloroaniline with 4 molar ratios have been synthesized [6].

There are three major processes described in the literature for the synthesis of aromatic polyesters. These are (a) an interfacial polycondensation of terephthaloyl chloride (TPCl) / isophthaloyl chloride (IPCl) with bisphenol-A (BPA) under phase transfer conditions,[7-9] (b) melt polycondensation of BPA-diacetate with terephthalic acid (TPA) /

isophthalic acid (IPA) in the presence of a catalyst[**10-12**], and (c) melt polycondensation of diphenyl terephthalate (DPT) / diphenyl isophthalate (DPI) with BPA in the presence of a catalyst. Because phase-transfer-catalysed polycondensation or interfacial polycondensation (IPC) is known to be useful on the synthesis of general aromatic polyesters and their analogs, this method has been employed by many investigators. The polyesters so obtained are in good yield with high molecular weights. Further the range of the polymers prepared is greater. The study has focuses on the silicate systems in artificial mineralized water, the micro-topography pictures of the silica scales were observed in different solutions [**13**] The IPC is a rapid polymerization process at the interface between water containing difunctional intermediate and an inert immiscible organic solvent containing a complementary difunctional reactant. In light of this, the IPC technique with stirring has been selected in the present work for the synthesis of polyesters formed from various types of aliphatic and aromatic diacid chlorides and different types of aromatic diols. Homopolymer of methyl methacrylate (MMA) and its copolymer using different compositions of styrene and 1-decene were synthesized [**14**].

Thus, the growth and expansion of polyester work, both basic and applied over the past few decades has been enormous. In an attempt to synthesize new polyesters by condensation of aliphatic and aromatic diacids or diacid chloride with aromatic diols with or without liquid crystalline structure, the present work was undertaken.

EXPERIMENTAL SECTION

Materials

Dicarboxylic Acids: Adipic acid (ADA) and sebasic acid (SEA) from SRL, Mumbai were used as received. Cyanuric chloride was obtained from ATUL, Valsad, having purity better than 98 mol% and was further purified by crystallization from pure benzene (mp 146°C). β -Naphthylamine was obtained from Polypharm and p-hydroxybenzaldehyde, p-aminophenol, benzidine, and p-phenylenediamine from SRL, Mumbai of purity better than 99% were used as received. Citramide (cityltriethylammoniumbromide) (SRL, Mumbai, extra-pure 99%) was used as received. Thionyl chloride, pyridine, ethanol, chloroform, methanol, acetone, sodium hydroxide, sodium bicarbonate, sulphuric acid, hydrochloric acid, etc. were good quality laboratory reagents and used after appropriate purification and distillation if required.

Acid Chloride Monomers: Adipoyl chloride (ADCl) and sebacyl chloride (SECl) were synthesized from the condensation reaction of their corresponding dicarboxylic acids with excess of thionyl chloride, in the presence of few drops of pyridine as a catalyst. They were purified by crystallization with n-hexane.

Aromatic Diol Monomers: Bisphenol-A (BPA) was obtained from Fluka, Switzerland, puris having purity > 97%. It was repeatedly crystallized from 50% aqueous acetic acid. The crystals were filtered thoroughly, washed with water and dried. It was used after recrystallization from benzene (mp 156° C). Resorcinol (RES) was obtained from SRL, Mumbai having purity better than 99%. It was purified by recrystallization from rectified spirit.

4,4'-Bishydroxy biphenyl thio ether (BHBPT) was obtained from United Phosphorous Ltd., Vapi, having purity better than 98% was used as received. The ¹H-NMR (Figure 1, CDCl₃, 250 MHz, TMS, δ ppm) for BHBPT: δ 6.70-6.74 (d, 4H, ortho- to -OH), 7.10-7.13 (d, 4H, ortho- to -S-), 9.39 (s, 2H, -OH).

1,5-Dihydroxynaphthalene (15DHN) was obtained from ATIC, Valsad, having a purity > 92% and was further purified by crystallization from ethanol (mp 195°C).

4,4'-Bis(hydroxy)benzilidene aniline (BHBA) was synthesized from reaction of p-hydroxybenzaldehyde and paminophenol. Ethanolic solution of p-hydroxybenzaldehyde (1.2 g, 0.01 mol) mixed with ethanolic solution of pamino phenol (1.09 g, 0.01 mol) was refluxed in water-bath for 2-3 hrs. The reaction mixture was poured in to crushed ice. The yellow precipitate separates out; it was filtered, washed with methanol and distilled water and dried (mp 194°C). FTIR (KBr, cm⁻¹) 3426 (broad O-H), 1615 (-CH=N), 1588 and 1510 (-C=C aromatic). ¹³C-NMR (Figure 2, DMSO-d6, TMS) δ ppm: 155.4-157.9 (C1, -C-OH), 115.2-117 (C2 & C8, ortho- to –OH), 128.4-128.7 (C3, ortho- to –CH=N), 130.1-132 (C4, -C-CH=N), 160-163.2 (C5, -CH=N), 122-122.4 (C6, -C-N=HC), 125.4 (C7, ortho- to –N=CH), 143.1-148.4 (C9, -C-OH).

4,4'-Bis(hydroxybenzilidene) benzidine (BHBB) was synthesized from reaction of p-hydroxybenzaldehyde and benzidine. Ethanolic solution of p-hydroxybenzaldehyde (2.4 g, 0.02 mol) mixed with ethanolic solution of

benzidine (1.84 g, 0.01 mol) was refluxed in water-bath for 2-3 hrs. The reaction mixture was poured in crushed ice. The yellow precipitate separates out. It was filtered, washed with methanol and distilled water and dried. FTIR (KBr, cm⁻¹) 3426 (broad O-H stretch), 1606 (-CH=N), 1594, 1510 and 1451 (-C=C- aromatic). ¹H-NMR (Figure 3,.DMSO-d6, 90 MHz, TMS) δ ppm 8.4 (d, 2H, 2CH=N), 6.60-6.95 (m, 4Ar-H, ortho to -OH), 7.15-7.50 (m, 4Ar-H, ortho to phenyl), 7.65-7.85 (m, 8Ar-H, ortho to azomethine and amino). ¹³C-NMR (Figure 4, DMSO-d6, TMS) δ ppm: 146.7-150.9 (C1, -C-OH), 114.2-115.5 (C2, ortho- to -OH), 127-127.6 (C3, ortho- to -CH=N), 130.5-130.6 (C4, -C-CH=N), 158.9-160.6 (C5, -CH=N), 128.7 (C6, -C-N=HC), 121.3-121.5 (C7, ortho- to -N=CH), 125.8-126.8 (C8, ortho- to -Ph), 136.6-137.9 (C9, -C-Ph).

4,4'-Bis(hydroxy benzilidine) p-phenylenediamine (BHBP) was synthesized from reaction of p-hydroxybenzaldehyde and p-phenylenediamine. Ethanolic solution of 2.44 g (0.02 mol) p-hydroxybenzaldehyde and ethanolic solution of 1.10 g (0.01 mol) p-phenylenediamine were mixed and refluxed in water-bath for 2-3 hrs. The reaction mixture was poured in crushed ice. The yellow precipitate separates; it was filtered, washed with methanol and distilled water and dried. The product was purified by reprecipitations from chloroform-methanol (Yield 81%, mp 260°C). The FT-IR: 3426 (broad O-H stretch), 1602 (-CH=N), 1591, 1513 and 1444 (-C=C aromatic). ¹³C-NMR (Figure 5, DMSO-d6, TMS, δ ppm): 149.2 (C1, -C-OH), 114.5-115.6 (C2, ortho- to -OH), 129.7-130.5 (C3, ortho- to -CH=N), 132 (C4, -C-CH=N), 159 - 160.5 (C5, -CH=N), 121.7 (C6, -C -N=HC), 127.6-128.1 (C7, ortho- to -N=CH).

Measurements

Elemental analysis for all polyesters, C, H and N were estimated by "Carlo Erba Elemental Analyzer".FT-IR spectra of all polymer samples have been scanned in KBr pellet on Perkin-Elmer RX2, IR spectrometer by KBr pellet technique. The ¹H-NMR spectra were taken in DMSO-d₆ as a solvent on Bruker DPX-200 Spectrometer at 200 MHz (RSIC, CDRI, Lucknow) with a sweep time of 10 minutes at room temperature. The internal reference used was TMS. The ¹³C-NMR spectra were also taken in DMSO-d₆ solvent using Bruker DRX-300 Spectrometer at 300 MHz (RSIC, CDRI, Lucknow). The viscosity measurements were carried out in DMF at $30\pm0.2^{\circ}$ C, using an Ubbelohde suspended-level viscometer. The thermogravimetric analysis was made with the Mettler TA-4000 system, incorporating TG-50 thermobalance and TA-11 microprocessor. The measurements were recorded in air at a heating rate 10° C/min. in N₂ atmosphere.

Conditions for polyester synthesis

In the present investigation interfacial polycondensation of diacid chloride with aromatic diol is used. It has been observed that the polymerization reaction is influenced by solvent system, and catalytic and surfactant additives. The choice of the organic solvent is critical since it affects several other polymerization factors such as the potential partition of reactants between the two phases, the diffusion of the reactants, reaction rate and the solubility, swelling or permeability of the growing polymer. Chloroform/water interface system has been employed for similar polymerization of this type. The polar aqueous phase contains enough NaOH to dissolve BPA completely as the active phenolate ion, leaving as little as possible undissociated BPA, which could be extracted by the organic phase. The non-polar chloroform phase is an excellent solvent for ADCl and oligomer formed in reaction, although not for polymer of high molecular weight. Two possible side reactions are the alkaline hydrolysis of -OH and dichlorocarbene formation by the action of aqueous NaOH/chloroform. The low solubility of ADCl in water serves to prevent it from hydrolysis by the alkali. Moreover, very slow rate of the side reactions, as compared to the polycondensation insure that neither the course of polymerization nor the hydrolysis are adversely affected.

Effect of Catalytic and Surfactant Additives

The surface-active agent is known to enhance the degree of polymerization in the interfacial production of polymer. This enhancement is brought about by improved mechanical mixing, increased interfacial area and consequently increased contact of the reactants, the degree of enhancement is expected to depend on the nature of the additive and indeed the use of emulsifier has been the subject of optimization of studies. Sometimes IPC, as type of nucleophilic displacement, are carried out with phase transfer catalyst generally small symmetric quaternary ammonium cations. It has been suggested that both surfactant and catalytic functions could be combined through the use of cationic surfactants, which as quaternary ammonium compounds, could also used in transfer of monomer between phases. Earlier work has indicated a higher molecular weight of the product when amount of cationic surfactant was used. In the present case we have used citramide as a cationic surfactant and phase transfer catalyst.

Considering the experience of previous investigators, the reactants ADCl and BPA were taken in equimolar ratio, using chloroform-water interphase system and citramide as phase transfer catalyst. The stirring was vigorous and continuous and the duration of reaction was 5 min. at 30°C. These are summarized in Table 1.

Polymerization

The reaction was carried out using mechanical stirrer with a switch to control the speed in a 250 ml beaker. An initial charge of 0.025 mol of NaOH dissolved in a total of 75 ml of water was stirred at a moderate speed with 0.0125 mol of BPA. 0.25 mg of additive, citramide (phase transfer catalyst) dissolved in 10 ml of water was added. The organic phase was prepared by dissolving 0.0125 mol ADCl in 35 ml of chloroform. The speed of the stirrer was raised to the maximum value, and the organic phase was introduced rapidly. Mixing was continued thereafter for 5 min even though the reaction mass turned to a semisolid paste and adhered to the walls of the container. Total of 5 min. was allowed to elapse so that the reaction presumably could continue for full time, as is known to occur in precipitates in mixed systems. At the end of the 5 min period stirring (which still in progress) was interrupted and acetone added to the beaker. After one minute of gentle stirring the polymer was filtered off and washed with acetone to remove unreacted monomers and chloroform. The moist product was returned to the container, stirred with distilled water to wash out excess alkali and salts, and then filtered. The water washing was repeated twice or more till it is free from impurities. The polymerized product was dried to constant weight in a vacuum oven at 40°C.

In the similar manner other polyesters were prepared adopting the same procedure outlined above selecting appropriate acid chloride and diol. Thirteen polyesters of, ADCl or SECl with aromatic diols BPA, RES, 15DHN, BHBA, BHBB, BHBP, and BHBPT reported in the present investigation have been synthesized by the above IPC technique and reaction conditions.

The polymerization reaction is representing as follows:





RESULTS AND DISCUSSION

Thirteen linear aliphatic-aromatic polyesters were synthesized by stirred interfacial polycondensations of various diacid chlorides and aromatic diols using chloroform/water interphase, citramide as phase transfer catalyst at 30°C as listed in Table 2. *Yield and Appearance*

Yields of the different polymer samples involving adipoyl moiety are in the range from 20 to 67% while those of sebacyl moiety are from 32 to 86% (Table 2). All the polyesters are solid powders and coloured depending upon the types of aromatic diol involved. The polyesters PAD3, PAD4, PSE3 and PSE4 are black powders while other polyesters are either brown to dark brown powders.

Elemental Analysis

The results of elemental analysis of present polyesters are given in Table 3 The observed percentage of C, H, and N contents in present polyesters are fairly in good agreement with those theoretically calculated based on the repeat units in the chain. This suggests that both monomers join alternatively in 1:1 mole ratio.

Solubility Behaviors

A study of solubility of polymers in different types of solvents is of great importance, both for processing the polymers and for the service of article made from them. Many films and synthetic fibers are produced from the solutions. The solubility behavior also provides additional information about polymer-polymer and polymer-solvent interactions. Relative solubilities in different solvents are summarized in Table 4. The polyesters PAD1, PAD2, PAD3, PAD4, PAD5, PAD6, PAD7 are soluble in DMF and THF at room temperature while in DMSO they dissolve only on heating. They are partially soluble in nitrobenzene (NB) and insoluble in chlorobenzene (CB), dimethylacetamide (DMA), dichloroethane (DCE), ethylacetoacetate (EAA), ethyl chloroacetate (ECA), methanol, ethanol, and petroleum ether.

The polyesters involving sebacic acid moiety PSE1, PSE2, PSE4, PSE5, and PSE7 are soluble in THF and in DMF except PSE6, which is only partially soluble in DMF on heating (Table 4). These all polyesters are only partially soluble in DMSO and NB even on heating except PSE4 and PSE7, which get dissolved in DMSO on heating.

Solution Viscosity

Intrinsic viscosity $[\eta]$ is a measure of hydrodynamic volume and depends on molecular weight as well as on the size of the polymer coil in a given solution. There are number of methods which have been used to calculate the intrinsic viscosity $[\eta]$ of polymer solutions. The intrinsic viscosities of present polymer samples determined in DMF at 30°C using Huggins equation [41], Kraemer equation [42], Schulz-Blaschke equation 43 and Martin equation 44 are given Table 5 along with Huggins KH, Kraemer KK, Schulz-Blaschke KSB and Martin KM constants.Study of Table 5 shows that in general, the values of $[\eta]$ in DMF at 30°C obtained by using the Schulz-Blaschke equation (3) are slightly higher than those of other three equations. Since, the difference between $[\eta]$ obtained by the various equations is not large, we have taken an average value of all the four equations, which is given, in the last column of the Table 5.

An examination of intrinsic viscosities (Table 5) of given polyesters reveals that **PAD4** has the highest solution viscosity and **PSE5** has the lowest. The intrinsic viscosities of the investigated polyesters are in the range from 0.160 to 0.229 dl/g and follows the sequence,

PAD4 > PSE1 = PSE2 > PAD6 > PAD5 = PAD7 > PAD1 > PSE4 > PSE3 > PSE5.

For the present polymer samples, the values of KH-KK are in the range 0.47 to 0.50, with an average value of 0.48 ± 0.01 . This average value of KH-KK is in excellent agreement with the theoretically predicted value of 0.5 [45]. Further, generally the values of KH (hydrodynamic constant) are > 0.30, indicating chloroform to be a good solvent for these polymers.

Spectral Characterization

FTIR spectrums all the present thirteen polyesters are shown in Figures 6 to 9 The formation of polyester is confirmed from the typical characteristic bands observed at $1726\pm16 \text{ cm}^{-1}$ (>C=O stretch in ester) and 1035 ± 32 and $1246\pm43 \text{ cm}^{-1}$ (C-O-C symmetric and asymmetric stretch) in all the presently investigated polyesters. In adipic acid or sebacic acid,>C=O stretch was observed at 1690 cm⁻¹ which on esterification has shifted to $1726\pm16 \text{ cm}^{-1}$ as expected. In all the polyesters the absorption band at $1473\pm13 \text{ cm}^{-1}$ indicates incorporation of $-(CH_2)_n$ - of adipic or sebasic carboxylate moiety. The different types of polyesters can be distinguished from each other by a few other characteristic absorption frequencies of involved aromatic diols.

The involvement of BPA moiety in PAD1 and PSE1 is indicated by a band at 1384 cm⁻¹ (isopropyl group and bands at 1612 and 1510 cm⁻¹ (aromatic C=C stretch). The presence of resorcinol moiety in PAD2 and PSE2 is confirmed due to bands at 1610 \pm 10 cm⁻¹ and 1500 \pm 10 cm⁻¹ (aromatic C=C stretch) and 900, 765, 683 cm⁻¹ (1,3- disubstituted benzene. The 15DHN moiety in PAD3 can be identified due to bands at 1675-1600 cm⁻¹ and 1575 cm⁻¹ because of ring stretching vibration of substituted naphthalene. It is difficult to separately identify BHBA, BHBB and BHBP as all these diols contain same aromatic or -CH=N- groups in one another. The presence of characteristic band for - CH=N- at 1610-1580 cm⁻¹ confirms the presence of benzilidine group. It may be noted that intensity of band varies as the number of -CH=N- are different in these polyesters. A weak band at 730 cm⁻¹ (C-S-C) and band at 1599 cm⁻¹ (C=C aromatic) show involvement of BHBPT in polyester.

¹H-NMR spectra of four selected polyesters PAD1, PAD4 PSE1 and PSE4 obtained in DMSO-d6 solvent on Bruker DPX-200 spectrometer at 200 MHz (RSIC, CDRI, Luknow) with a sweep time of 10 minutes, at room temperature are shown in Figs. 10 to 13. The internal reference used was TMS.

PAD1 (Figure 10): 4H of two -CH₂- and 4H of two -CH₂O- in adipoyl moiety appears at δ 1.51 ppm and at 2.26 ppm, respectively. A sharp singlet at δ 1.59 ppm is indicative of 6H of isopropyl unit ^{56,57} and two doublets in the range of 6.60-6.62 and 6.94-6.97 ppm corresponds to 4 Ar-H (o- to isopropyl group) and 4 Ar-H (m- to isopropyl group) in BPA segment. **PAD4** (Figure 11): 4H of two -CH₂- and 4H of two -CH₂O- in adipoyl moiety appear at δ 1.61 ppm and at 2.26 ppm, respectively. Multiplet in the range of 6.79 to 7.76 ppm corresponds to 8Ar-H of BHBA segment. 4Ar-H ortho- to OC=O link, and 2Ar-H ortho- to amino + 2Ar-H ortho- to benzilidine groups resonate around 7.25-7.76, and 6.90-7.12⁵⁸, respectively. A singlet at δ 9.77 ppm is due to 1H of -CH=N-. small peak at 6.70-6.79 ppm is due to 2Ar-H, ortho- to residual end –OH group of BHBA moiety. **PSE1** (Figure 12): 12H (a,b) of 6 -CH₂- and 4H(c) of two -CH₂CO- of sebacyl moiety appear at δ 1.23-1.51 and at 2.17 ppm, respectively. A sharp singlet at δ 1.57 ppm is indicative of 6H of isopropyl unit ^{56,57} and two doublets in the range of 6.60-6.63 and 6.94-6.97 ppm corresponds to 4 Ar-H (o- to isopropyl group) and 4 Ar-H (m- to isopropyl group) in BPA segment. **PSE4** (Figure 13): 12H(a,b) of 6 -CH₂-, 4H(c) of two -CH₂C=O- of sebacyl moiety appear at δ 1.22-1.45 and at 2.14 ppm, respectively. Multiplet in the range of 6.86 to 7.73 ppm corresponds to 8Ar-H of BHBA segment. **4Ar**-H ortho-OC=O (ester), and 2Ar-H ortho- to amino + 2Ar-H ortho- to benzilidine groups resonate around 7.37-7.73, 6.86-7.31 ppm, respectively. A singlet at δ 8.9 ppm is due to 1H of -CH=N-. ⁵⁸ A small peak at 6.66 ppm is attributed to Ar-H ortho- to residual end –OH group of BHBA moiety.

Thermal gravimetric analysis:

Thermograms for the two investigated polyester samples: PAD1 and PSE1 are shown in Figure 14 From these thermograms initial decomposition temperature (T_i), temperature for maximum rate of decomposition (T_{max}) and half volatilization temperature T_{50} and integral procedural decomposition temperature (IPDT) have been summarized in Table 6. Qualitative behaviour of each of these thermograms has been described.

PAD1 (Figure.14a): Thermogram indicates the two-step degradation of PAD1. In the first step in the temperature range 174°C to 319°C only 8.5% weight loss occurred. The second step degradation from 319 to 496°C has accounted for 77.8% weight loss. The temperature at which maximum degradation of polyester PAD1 took place in

this step was 395°C. The temperature at which 50% weight of polymer degraded was 379°C. At 700 °C temperature 14.8% residue was left behind.

PSE1 (Figure 14b): It exhibits three-step thermal degradation. The first step decomposition started at 161° C, which extended up to 331° C, accounting for about 33.7% weight loss. The second step degradation from 331 to 490° C has accounted for 28.8% weight loss and in the third step degradation from 490° C to 635° C about 29.6% weight was lost. The maximum rates of weight loss occurred at 268, 388 and 550° C in the first, second and third step, respectively. 50% of the polyester weight loss occurred at 407° C. The residue left behind at 700° C was 7.6%.

Table 1. Reaction conditions for the synthesis of polyester from ADCl and BPA

Interface System	:	Chloroform/Water
Phase volume ratio	:	35 ml/ 85 ml
Reactants	:	ADCl = 0.0125 mol
		BPA = 0.0125 mol
Acid acceptor	:	0.025 mol NaOH
Additive	:	Citramide
Temperature	:	30°C
Time	:	5 min.
Stirring	:	Vigorous and continuous

Table 2. Polyesters obtained by the interfacial polycondensation technique from different aliphatic diacid chlorides with aromatic diols





Table 3. Elemental analysis C, H, and N % contents in the polyesters

Delvester	С	%	H	%	N%		
roiyester	calc.	obs.	Calc.	obs.	calc.	obs.	
PAD1	74.55	74.51	6.50	6.41	-	-	
PAD2	62.88	62.78	5.24	5.14	-	-	
PAD3	71.11	71.03	5.18	5.08	-	-	
PAD4	70.58	70.29	5.30	5.19	4.33	4.03	
PAD5	76.49	76.31	5.17	5.02	5.57	5.25	
PAD6	73.23	72.92	5.20	5.11	6.57	6.28	
PAD7	65.45	65.31	5.45	5.35	-	-	
PSE1	78.12	78.03	5.20	5.08	-	-	
PSE2	69.56	69.36	7.24	7.14	-	-	
PSE3	71.87	71.59	7.81	7.58	-	-	
PSE4	72.80	72.56	6.64	6.59	3.69	3.58	
PSE5	77.41	77.21	6.09	5.98	6.01	5.84	
PSE6	74.67	74.54	6.27	6.19	5.80	5.63	

	Table 4.	Relative	solubilities	of Polye	esters in	different	solvents	at 30°
--	----------	----------	--------------	----------	-----------	-----------	----------	--------

Colvent	polyesters of ADCl + aromatic diol								polyesters of SECl + aromatic diols					
Solvent	PAD1	PAD2	PAD3	PAD4	PAD5	PAD6	PAD7	PSE1	PSE2	PSE4	PSE5	PAD6	PAD7	PSE1
THF	S	S	S	S	S	S	S	S	S	S	S	S	S	S
DMF	S	S	S	S	S	S	S	S	S	S	S	PS	S	S
DMSO	SH	SH	SH	SH	SH	SH	SH	PS	PS	SH	PS	PS	SH	PS
Nitrobenzene	PS	PS	PS	PS	PS	PS	PS	PS	PS	PS	PS	PS	PS	PS
Chlorobenzene	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS
DMA	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS
Dichloroethane	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS
Chloroform	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS
ECA	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS
EAA	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS
Methanol	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS
Ethanol	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS
Petroleum ether	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS
Water	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS	IS

Table 5 Intrinsic viscosity in dl/g and Huggins K_H, Kraemer K_K, Schulz-Blaschke K_{SB} and Martin K_M constants for polyesters in DMF at 30°C

	Eq (1)		Eq (2)		Eq (3)		Eq (4)		
CODE	[η]	Кн	[η]	- K _K	[η]	K _{SB}	[η]	Км	<η>
PAD1	0.136	0.261	0.346	0.228	0.136	0.250	0.135	0.255	0.188
PAD4	0.229	0.313	0.229	0.182	0.230	0.289	0.230	0.300	0.229
PAD5	0.207	0.220	0.206	0.253	0.207	0.209	0.207	0.215	0.206
PAD6	0.218	0.245	0.217	0.234	0.218	0.230	0.218	0.237	0.218
PAD7	0.207	0.223	0.206	0.252	0.207	0.211	0.207	0.217	0.206
PSE1	0.222	0.254	0.221	0.226	0.222	0.238	0.222	0.246	0.222
PSE2	0.221	0.329	0.221	0.168	0.221	0.305	0.221	0.315	0.221
PSE3	0.172	0.238	0.172	0.244	0.172	0.227	0.172	0.232	0.172
PSE4	0.179	0.272	0.179	0.215	0.179	0.256	0.179	0.264	0.179
PSE5	0.160	0.259	0.160	0.228	0.160	0.247	0.160	0.253	0.160

Table 6 Thermal behavior of polyesters in air

Polymer	Step	T₁ °C	T _{max} °C	T _f °C	T ₁₀ °C	T ₅₀ °C	IPDT °C	Residue %
PAD1	I II	174 319	192 395	319 496	234	379	338	14.8
PSE1	I II III	161 331 490	268 388 550	331 490 635	234	407	356	7.6

CONCLUSION

The investigated linear aliphatic-aromatic polyesters show excellent solubility in DMF and THF at ambient temperature. They are partially soluble in DMSO and NB. However, in many cases they dissolve in DMSO on the heating. The intrinsic viscosity of linear aliphatic-aromatic polyesters varies in the range of 0.160-0.229 dl/g at 30°C. The IR a spectra of polyester is confirmed in the linear aliphatic aromatic polyesters from the typical characteristic bands observed at 1726±16 (>C=O stretch in ester) and 1035±32 and 1246±43 (C-O-C symmetric and asymmetric stretch).High-resolution ¹H-NMR spectra of four selected aliphatic-aromatic polyesters PAD1, PAD4, PSE1 and PSE4 were consistent with the structure of repeat unit in corresponding polyesters. The thermal behavior of polyester have modest to good thermal stability. From this study it can be seen that the thermal stability is highly dependent on the type of diacid and/or diol moieties and their chemical structure. It is found that by replacing aromatic rings in place of aliphatic chain in the polyester, the thermal stability can be enhanced significantly.

REFERENCES

[1] Seymour, R.B., Kirshenbaum G.S, editors. *High performance polymers: their origin and development*. New York: Elsevier; **1986**.

[2] Han, H., Bhowmik P.K. Prog Polym Sci; 22:1431–502, 1997.

[3] Jadhav, J.Y., Kantor, S.W. In: Kroschwitz JI, editor. High performance polymers and composites. New York: Wiley; 1991.

[4] Cassidy, P.A. Thermally stable polymers. New York: Dekker; 1980.

[5] Wasudeo. B. Gurnule and Sonali P. Dhote, *Journal of Chemical and Pharmaceutical Research*, 5(12), 942-949, **2013.**

[6] A. D. Borkar, Journal of Chemical and Pharmaceutical Research, 4(7), 3526-3528, 2012.

[7] Mitsubishi Chemical Corporation Ltd. Japan, Jpn. Kokai Tokkyo Koho JP 82, 96,017 (**1980**), CA 97, 163706b (**1982**).

[8] Mitsubishi Chemical Corporation Ltd. Japan, *Jpn. Kokai Tokkyo Koho JP 59*, 223,721, 59, 223722 (**1983**), *CA* 102, 204497b, 204498c (**1985**).

[9] Mitsubishi Chemical Corporation Ltd. Japan, Jpn. Kokai Tokkyo Koho JP 60, 23,420 (1983), CA 103, 6875f (1985).

[10] Berzer, M.H., Maresca, L.M., and Steiner, U.A. Eur. Pat. Appl. EP 35,269 (1981) to Union Carbide Corp., USA, CA 96, 20601g (1982).

[11] Berzer, M.H., Maresca, L.M., and Ulrich, A. U.S. Pat. 4, 374,239 (1983) to Union Carbide Corp., USA, CA 98, 161355h (1983).

[12] Yu M.C., U.S. Pat. 4, 485,230 (1984) to Philips Petroleum Co., USA, CA 102, 46468m (1985).

[13] Xin Sui, Yu Liu, Baohui Wang, Haiming Wu and Jing Dong, Journal of Chemical and Pharmaceutical Research, 6(1), 681-685, 2014.

[14] Pranab Ghosh, Debabrata Nandi and Tapan Das, *Journal of Chemical and Pharmaceutical Research*, 2(4), 122-133, **2010.**